

O-Ring Sizes



KRS Part No.	AS-568 Part No.	Inner Dia	Tolerance	Cross Section	Tolerance
10-07	001	0.74	0.10	1.02	0.08
13-11	002	1.07	0.10	1.27	0.08
15-14	003	1.42	0.10	1.52	0.08
18-18	004	1.78	0.13	1.78	0.08
18-26	005	2.57	0.13	1.78	0.08
18-29	006	2.90	0.13	1.78	0.08
18-37	007	3.68	0.13	1.78	0.08
18-45	008	4.47	0.13	1.78	0.08
18-53	009	5.28	0.13	1.78	0.08
18-60	010	6.07	0.13	1.78	0.08
18-76	011	7.65	0.13	1.78	0.08
18-92	012	9.25	0.13	1.78	0.08
18-108	013	10.82	0.13	1.78	0.08
18-124	014	12.42	0.13	1.78	0.08
18-140	015	14.00	0.13	1.78	0.08
18-156	016	15.60	0.13	1.78	0.08
18-171	017	17.17	0.23	1.78	0.08
18-188	018	18.77	0.23	1.78	0.08
18-203	019	20.35	0.23	1.78	0.08
18-220	020	21.95	0.23	1.78	0.08
18-235	021	23.52	0.23	1.78	0.08
18-252	022	25.12	0.25	1.78	0.08
18-267	023	26.70	0.25	1.78	0.08
18-283	024	28.30	0.25	1.78	0.08
18-299	025	29.87	0.25	1.78	0.08
18-315	026	31.47	0.28	1.78	0.08
18-330	027	33.05	0.28	1.78	0.08
18-346	028	34.65	0.33	1.78	0.08
18-378	029	37.82	0.33	1.78	0.08
18-409	030	41.00	0.33	1.78	0.08
18-442	031	44.17	0.38	1.78	0.08
18-473	032	47.35	0.38	1.78	0.08
18-505	033	50.52	0.46	1.78	0.08
18-533	034	53.30	0.46	1.78	0.08
18-568	035	56.87	0.46	1.78	0.08
18-600	036	60.05	0.46	1.78	0.08
18-628	037	62.80	0.46	1.78	0.08
16-665	038	66.40	0.51	1.78	0.08
18-696	039	69.57	0.51	1.78	0.08
18-728	040	72.75	0.51	1.78	0.08
18-759	041	75.92	0.61	1.78	0.08
18-823	042	82.27	0.61	1.78	0.08
18-886	043	88.62	0.61	1.78	0.08
18-950	044	94.97	0.69	1.78	0.08
18-1013	045	101.32	0.69	1.78	0.08
18-1077	046	107.67	0.76	1.78	0.08
18-1140	047	114.02	0.76	1.78	0.08
18-1204	048	120.37	0.76	1.78	0.08
18-1267	049	126.72	0.94	1.78	0.08
18-1330	050	133.07	0.94	1.78	0.08

*** ALL DIMENSIONS ARE IN MM**