



O-Ring Sizes

KRS Part No.	AS-568 Part No.	Inner Dia	Tolerance	Cross Section	Tolerance
53-1105	348	110.49	0.76	5.33	0.13
53-1137	349	113.67	0.76	5.33	0.13
53-1169	350	116.84	0.76	5.33	0.13
*53-1175	----	117.50	0.76	5.33	0.13
53-1206	351	120.65	0.76	5.33	0.13
53-1238	352	123.80	0.76	5.33	0.13
53-1264	353	126.37	0.94	5.33	0.13
53-1295	354	129.54	0.94	5.33	0.13
53-1327	355	132.72	0.94	5.33	0.13
53-1359	356	135.89	0.94	5.33	0.13
53-1397	357	139.69	0.94	5.33	0.13
53-1425	358	142.69	0.94	5.33	0.13
53-1455	359	145.42	0.94	5.33	0.13
53-1486	360	148.59	0.94	5.33	0.13
53-1518	361	151.77	0.94	5.33	0.13
53-1581	362	158.12	1.02	5.33	0.13
53-1645	363	164.47	1.02	5.33	0.13
53-1708	364	170.82	1.02	5.33	0.13
53-1772	365	177.17	1.02	5.33	0.13
53-1835	366	183.52	1.14	5.33	0.13
53-1899	367	189.87	1.14	5.33	0.13
53-1962	368	196.22	1.14	5.33	0.13
53-2026	369	202.57	1.14	5.33	0.13
53-2089	370	208.92	1.27	5.33	0.13
53-2153	371	215.27	1.27	5.33	0.13
53-2261	372	221.62	1.27	5.33	0.13
53-2280	373	227.97	1.27	5.33	0.13
53-2343	374	234.32	1.40	5.33	0.13
53-2407	375	240.67	1.40	5.33	0.13
53-2470	376	247.02	1.40	5.33	0.13
53-2534	377	253.37	1.40	5.33	0.13
53-2661	378	266.07	1.52	5.33	0.13
53-2788	379	278.77	1.52	5.33	0.13
53-2915	380	291.47	1.65	5.33	0.13
53-3042	381	304.17	1.65	5.33	0.13
53-3295	382	329.57	1.65	5.33	0.13
53-3550	383	354.97	1.78	5.33	0.13
53-3804	384	380.37	1.78	5.33	0.13
53-4053	385	405.26	1.91	5.33	0.13
53-4307	386	430.66	2.03	5.33	0.13
53-4561	387	456.06	2.16	5.33	0.13
53-4814	388	481.41	2.29	5.33	0.13
53-5068	389	506.81	2.41	5.33	0.13
53-5322	390	532.21	2.41	5.33	0.13
53-5576	391	557.61	2.54	5.33	0.13
53-5827	392	582.68	2.67	5.33	0.13
53-6081	393	608.08	2.79	5.33	0.13
53-6335	394	633.48	2.92	5.33	0.13
53-6589	395	658.88	3.05	5.33	0.13
70-1137	425	113.67	0.84	6.99	0.15
70-1168	426	116.84	0.84	6.99	0.15

*** ALL DIMENSIONS ARE IN MM**